

**SuperSafe™**  
T

---

*BATTERY  
PERFORMANCE DATA*

---



**EnerSys®**

*Power/Full Solutions*

RESERVE  
POWER





















Discharge Rates in Watts per Cell to 1.80Vpc at 20°C

Table with columns for Battery Type, Minutes (5-55), and Hours (1-24). Rows include battery types such as 12T45, 12T55, 12T70, 12T80, 4T105, 6T105, 6T130, 4T155, 6T155, 6T165/2, 2T200, 4T230, 2T275, 2T310, 2T320, 2T400/2, 2T460/4, 2T460/6, 2T500/2, and 2T500/6.

Discharge Rates in Watts per Cell to 1.85Vpc at 20°C

Table with columns for Battery Type, Minutes (5-55), and Hours (1-24). Rows include battery types such as 12T45, 12T55, 12T70, 12T80, 4T105, 6T105, 6T130, 4T155, 6T155, 6T165/2, 2T200, 4T230, 2T275, 2T310, 2T320, 2T400/2, 2T460/4, 2T460/6, 2T500/2, and 2T500/6.



[www.enersys.com](http://www.enersys.com)

**EnerSys**  
P.O. Box 14145  
Reading, PA 19612-4145  
USA  
Tel: +1-610-208-1991  
+1-800-538-3627  
Fax: +1-610-372-8613

**EnerSys Europe**  
Löwenstrasse 32  
8001 Zurich,  
Switzerland

**EnerSys Asia**  
152 Beach Road  
Gateway East Building  
Level 11  
189721 Singapore  
Tel. +65 6508 1780

Contact:  
**Light Technologies Co., Ltd.**  
Tel: +86-755-61289329  
Fax: +86-755-61624455  
[www.light-corp.cn](http://www.light-corp.cn)

© 2010 EnerSys. All rights reserved.  
Trademarks and logos are the property of  
EnerSys and its affiliates unless otherwise noted.